

# Adding Properties to Triples in AllegroGraph

AllegroGraph provides two ways to add metadata to triples. The first one is very similar to what typical property graph databases provide: we use the named graph of triples to store meta data about that triple. The second approach is what we have termed *triple attributes*. An attribute is a key/value pair associated with an individual triple. Each triple can have any number of attributes. This approach, which is built into AllegroGraph's storage layer, is especially handy for security and bookkeeping purposes. Most of this article will discuss triple attributes but first we quickly discuss the named graph (i.e. fourth element or quad) approach.

## 1.0 The Named Graph for Properties

Semantic Graph Databases are actually defined by the W3C standard to store RDF as 'Quads' (Named Graph, Subject, Predicate, and Object). The 'Triple Store' terminology has stuck even though the industry has moved on to storing quads. We believe using the named graph approach to store metadata about triples is richer model than the property graph database method.

The best way to understand this is to give an example. Below we see two statements about Bruce weighing 105 kilos. The triple portions (subject, predicate, object) are identical but the named graphs (fourth elements) differ. They are used to provide additional information about the triples. The graph values are S1 and S2. By looking at these graphs we see that


- The author of the first triple (with graph S1) is Sophia and the author of the second (with graph S2) is Bruce (who is also the subject of the two triples).

- Sophia is 100% certain about her statement while Bruce is only 10% certain about his.

Using the named graph we can do even more than a property graph database, as the value of a graph can itself be a node, and is the subject of various triples which specify the original triple's author, date, and certainty. Additional triples tell us the ages of the authors and the fact that the authors are married.

Subject	Predicate	Object	Graph
Bruce	Weighs	105kg	S1
Bruce	Weighs	105kg	S2
Bruce	Age	45	None
Bruce	<u>MarriedTo</u>	Sophia	None
S1	Author	Sophia	None
S1	Date	2012-12-12T08:00:00	None
S1	Certainty	100 %	None
S2	Author	Bruce	None
S2	Date	2012-12-12T08:00:00	None
S2	certainty	10%	None
Sophia	Age	47	None

Here is the data displayed in Gruff, AllegroGraph's associated triple store browser:



Using named graphs for a triple's metadata is a powerful tool but it does have limitations: (1) only one graph value can be associated with a triple, (2) it can be important that metadata is stored directly and physically with the triple (with named graphs, the actual metadata is usually stored in additional triples with the graph as the subject, as in the example above), and (3) named graphs have competing uses and may not be available for metadata.

## 2.0 The Triple Attributes approach

AllegroGraph uniquely offers a mechanism called *triple attributes* where a collection of user defined key/value pairs can be stored with each individual triple. The advantage of this approach is manifold, but the original use case was designed for triple level security for an Intelligence agency.

By having triple attributes physically connected to the triples in the storage layer we can provide a very powerful and flexible mechanism to protect triples at the lowest

possible level in AllegroGraph's architecture. Our first example below shows this use case in great detail. Other use cases are for example to add weights or costs to triples, to be used in graph algorithms. Or we can add a recorded time or expiration times to a triple and use that to provide a time machine in AllegroGraph or do automatic clean-up of old data.

### Example with Attributes:

Subject – <[http://dbpedia.org/resource/Arif\\_Babayev](http://dbpedia.org/resource/Arif_Babayev)>

Predicate – <<http://dbpedia.org/property/placeOfDeath>>

Object – <<http://dbpedia.org/resource/Baku>>

Named Graph – <<http://ex#trans@@1142684573200001>>

Triple Attributes – {"securityLevel": "high",  
"department": "hr", "accessToken": ["E", "D"]}

This article provides an initial introduction to attributes and the associated concept of static filters, showing how they are set up and used. We start with a security example which also describes the basics of adding attributes to triples and filtering query results based on attribute values. Then we discuss other potential uses of attributes.

## 2.1 Triple Attribute Basics: a Security Example

One important purpose of attributes, when they were added as a feature, was to allow for very fine triple-level security, so that triples would be visible or invisible to users according to the attributes of the triples and the permissions associated with the query being posed by the user.

Note that users as such do not have attributes. Instead, attribute values are assigned when a query is posed. This is

an important point: it is natural to think that there can be an attribute SECURITY-LEVEL, and a triple can have attribute SECURITY-LEVEL=3, and USER1 can have an attribute SECURITY-LEVEL=2 and USER2 can have an attribute SECURITY-LEVEL=4, and the system can require that the user SECURITY-LEVEL attribute must be greater than the triple SECURITY-LEVEL for the triple to be visible to the user. But that is not how attributes work. The triples can have the attribute SECURITY-LEVEL=2 but users do not have attributes. Instead, the filter is made part of the query.

Here is a simple example. We define attributes and static attribute filters using AGWebView. We have a repository named repo. Here is a portion of its AGWebView page:

## Repository repo — 0 statements

[\[edit description\]](#)

### Load and Delete Data

- [Add a statement](#)
- [Delete statements](#)
- [Import RDF:](#)
  - [from an uploaded file](#)
  - [from a server-side file](#)
  - [from a text area input](#)

### Explore the Repository

- [View triples](#)
- [View quads](#)
- [View repository's classes](#)
- [View repository's predicates](#)
- [View repository's named graphs](#)

### Reports

- [Storage report](#)
- [Triple indices](#)
- [String table](#)
- [Full list of reports ...](#)


### Multi-Master Replication

- [Convert store to a replication instance](#)

### Warm Standby Replication

- [Control replication](#)

### Repository Control

- [Export repository as](#)
- [Start a session](#) — support transactions and Prolog functors
- [Warmup store](#)
- [Back-up this repository](#)
- [Export duplicate statements](#)
- [Delete duplicate statements](#)
- [Suppress duplicate statements](#)
- [View active transactions](#)
- [Recognize geospatial datatypes automatically:](#) ☐
- [Control durability \(bulk-load mode\)](#)
- [Manage attribute definitions](#)
- [Set static attribute filter](#)
- [Manage triple indices](#)
  - [Optimize the repository](#) 



The red arrow points to the commands of interest: Manage attribute definitions and Set static attribute filter. We click on Set static attribute filter to define an attribute. We have filled in the attribute information (name *security-level*, minimum and maximum number allowed per triple, allowed values, and whether order or not (yes in our case):

AllegroGraph WebView

repository repo

[Repository](#) | [Queries](#) | [Utilities](#) | [Admin](#) | [User test](#)

New Attribute

Name

security-level

Min. number

0

Max. number

1

Allowed Values

0,1,2,3,4,5

Ordered

☒

Save

Cancel

Attribute Definitions

+ Add New

Name	Min. number	Max. number	Allowed values	Ordered	
No attributes have been defined					

We click Save and the attribute is defined:

AllegroGraph WebView

repository repo

[Repository](#) | [Queries](#) | [Utilities](#) | [Admin](#) | [User test](#)

Attribute Definitions

+ Add New

Name	Min. number	Max. number	Allowed values	Ordered	
security-level		1	0,1,2,3,4,5	✓	

Then we define a filter (on the Set static attribute filter page) :

AllegroGraph WebView

repository repo

[Repository](#) | [Queries](#) | [Utilities](#) | [Admin](#) | [User test](#)

Static Filter

Current filter

```
(attribute-set> user.security-level triple.security-level)
```

Edit filter

```
(attribute-set> user.security-level triple.security-level)
```

Save

Revert to current

Clear

We defined the filter `(attribute-set> user.security-level triple.security-level)` and clicked Save (the definition appears in both the Edit and the Current fields). The filter says that the “user” security level must be greater than the triple security level. We put “user” in quotes because the user security level is specified as part of the query, and has no direct connection to any specific user.

Here are some triples in a nqx file *fr.nqx*. The first triple has no attributes and the other three each has a security-level attribute value.

[<http://www.franz.com#emp0>](http://www.franz.com#emp0)



```
<http://www.franz.com#position> "intern" .
```

```
<http://www.franz.com#emp1>
```

```
<http://www.franz.com#position> "worker" {"security-level":  
"2"} .
```

```
<http://www.franz.com#emp2>
```

```
<http://www.franz.com#position> "manager" {"security-level":  
"3"} .
```

```
<http://www.franz.com#emp3>
```

```
<http://www.franz.com#position> "boss" {"security-level": "4"}  
.
```

We load this file into a repository which has the security-level attribute defined as above and the static filter mentioned above also defined. (Triples with attributes can also be entered directly when using AGWebView with the Import RDF from a text area input command).

Once the triples are loaded, we click View triples in AGWebView and we see no triples:

**AllegroGraph WebView** repository repo

[Repository](#) | [Queries](#) | [Utilities](#) | [Admin](#) | [User test](#)

### Edit query

1 # View triples

2 SELECT ?s ?p ?o { ?s ?p ?o . }

Execute

Log Query

Show Plan

Save as

Add to repository

No results

This result is often surprising to users just beginning to work with attributes and filters, who may expect the first triple, abbreviated to [emp0 position intern], to be visible, but the system is doing what it is supposed to do. It will only show triples where the security-level of the user posing the query is greater than the security level of the triple. The user has no security level and so the comparison fails, even with triples that have no security-level attribute value. We will describe below how to ensure you can see triples with no attributes.

So we need to specify an attribute value to the user posing the query. (As said above, users do not themselves have attribute values. But the attribute value of a user posing a query can be specified as part of the query.) “User” attributes are specified with a prefix like the following:

prefix franzOption\_userAttributes: <franz:%7B%22security-

```
level%22%3A%223%22%7D>
```

so the query should be

```
prefix franzOption_userAttributes: <franz:%7B%22security-  
level%22%3A%223%22%7D>
```

```
select ?s ?p ?o { ?s ?p ?o . }
```

We will show the results below, but first what are all the % signs and numbers doing there? Why isn't the prefix just `prefix franzOption_userAttributes: <franz:{"security-level":"3"}>`? The issue is that `{"security-level":"3"}` won't read correctly. It must be URL encoded. We do this by going to <https://www.urlencoder.org/> (there are other websites that do this as well) and put `{"security-level":"3"}` in the first box, click Encode and get `%7B%22security-level%22%3A%223%22%7D`. We then paste that into the query, as shown above.

When we try that query in AGWebView, we get one result:

AllegroGraph WebView

repository repo

[Repository](#) | [Queries](#) | [Utilities](#) | [Admin](#) | [User test](#)

Edit query

```

1 prefix franzOption_userAttributes: <franz:%7B%22security-level%22%3A%225%22%7D>
2 select ?s ?p ?o { ?s ?p ?o . }
3

```

Execute

Log Query

Show Plan

Save as

Add to repository

1 Result in 2.619 ms

Information

s	p	o
<http://www.franz.com#emp1>	<http://www.franz.com#position>	"worker"

If we encode {"security-level": "5"} to get the query

```

prefix  franzOption_userAttributes:  <franz:%7B%22security-
level%22%3A%225%22%7D>
select ?s ?p ?o { ?s ?p ?o . }

```

we get three results:

emp3	position	"boss"
emp2	position	"manager"
emp1	position	"worker"

since now the "user" security-level is greater than that of any triples with a security-level attribute. But what about

the triple with subject emp0, the triple with no attributes? It does not pass the filter which required that the user attribute be greater than the triple attribute. Since the triple has no attribute value so the comparison failed.

Let us redefine the filter to:

```
(or (attribute-set> user.security-level triple.security-level)
    (empty triple.security-level))
```

The screenshot shows the AllegroGraph WebView interface. At the top, there is a header bar with the title "AllegroGraph WebView" and a sub-header "repository repo". Below this is a navigation bar with links: "Repository", "Queries", "Utilities", "Admin", and "User test". The main content area is titled "Static Filter". It contains two sections: "Current filter" and "Edit filter". Both sections display the same filter expression: 

```
(or (attribute-set> user.security-level triple.security-level)
    (empty triple.security-level))
```

. At the bottom of the "Edit filter" section, there are three buttons: "Save", "Revert to current", and "Clear".

Now a triple will pass the filter if either (1) the “user” security-level is greater than the triple security-level or

(2) the triple does not have a security-level attribute. Now the query from above where the user has attribute security-level:"5" will show all the triples with security-level less than 5 and with no attributes at all. That happens to be all four triples so far defined:

**AllegroGraph WebView** repository repo

Repository | Queries | Utilities | Admin | User test

Edit query

```
1 prefix franzOption_userAttributes: <franz:%7B%22security-level%22%3A%225%22%7D>
2 select ?s ?p ?o { ?s ?p ?o . }
3
```

Execute Log Query Show Plan Save as Add to repository

4 Results in 0.286 ms Information

s	p	o
<http://www.franz.com#emp0>	<http://www.franz.com#position>	"intern"
<http://www.franz.com#emp3>	<http://www.franz.com#position>	"boss"
<http://www.franz.com#emp2>	<http://www.franz.com#position>	"manager"
<http://www.franz.com#emp1>	<http://www.franz.com#position>	"worker"

## The triple

emp0      position      "intern"

will now appears as a result in any query where it satisfies the SPARQL select regardless of the security-level of the

“user”.

It would be a useful feature that we could associate attributes with actual users. However, this is not as simple as it sounds. Attributes are features of repositories. If I have a REP01 repository, it can have a bunch of defined attributes and filters but my REP02 may know nothing about them and its triples may not have any attributes at all, and no attributes are defined, and (as a result) no filters. But users are not repository-linked objects. While a repository can be made read-only or unreadable for a user, users do not have finer repository features. So an interface for providing users with attributes, since it would only make sense on a per-repository basis, requires a complicated interface. That is not yet implemented (though we are considering how it can be done).

Instead, users can have specific prefixes associated with them and that prefix and be included in any query made by the user.


But if all it takes to specify “user” attributes is to put the right line at the top of your SPARQL query, that does not seem to provide much security. There is a feature for users “Allow user attributes via SPARQL PREFIX `franzOption_userAttributes`” which can restrict a user’s ability to specify “user” attributes in a query, but that is a rather blunt instrument. Instead, the model is that most users (outside of trusted administrators) are not actually allowed to pose SPARQL queries directly. Instead, there is an intermediary program which takes the query a user requests and, having determined the status of the user and what attribute values should be given to the user, modifies the query with the appropriate `franzOption_userAttributes` prefixes and then sends the query on to the server, following which it captures the results and

sends them back to the requesting user. That intermediate program will store the prefix suitable for a user and thus associate “user” attributes with specific users.

## 2.2 Using attributes as additional data

Although triple security is one powerful use of attributes, security is far from the only use. Just as the named graph can serve as additional data, so can attributes. SPARQL queries can use attribute values just as static filters can filter out triples before displaying them. Let us take a simple example: the attribute `timeAdded`. Every triple we add will have a `timeAdded` attribute value which will be a string whose contents are a datetime value, such as “2017-09-11T:15:52”. We define the attribute:

### Attribute Definitions

<a href="#">+ Add New</a>					
Name	Min. number	Max. number	Allowed values	Ordered	
timeAdded	1	1			

Now let us define some triples:

```
<http://www.franz.com#emp0>
<http://www.franz.com#callRank> "2" {"timeAdded":
"2019-01-12T10:12:45" } .
<http://www.franz.com#emp0>
<http://www.franz.com#callRank> "1" {"timeAdded":
"2019-01-14T14:16:12" } .
<http://www.franz.com#emp0>
<http://www.franz.com#callRank> "3" {"timeAdded":
"2019-01-11T11:15:52" } .
```



```

    <http://www.franz.com#emp1>
<http://www.franz.com#callRank> "5" {"timeAdded":
"2019-01-13T11:03:22" } .
    <http://www.franz.com#emp0>
<http://www.franz.com#callRank> "2" {"timeAdded":
"2019-01-13T09:03:22" } .

```

We have a call center with employees making calls. Each call has a ranking from 1 to 5, with 1 the lowest and 5 the highest. We have data on five calls, four from emp0 and one from emp1. Each triples has a timeAdded attribute with a string containing a dateTime value. We load these into a empty repository named at-test where the timeAdded attribute is defined as above:



SPARQL queries can use the attribute magic properties (see <https://franz.com/agraph/support/documentation/current/triple-attributes.html#Querying-Attributes-using-SPARQL>). We use the attributesNameValue magic property to see the subject, object, and attribute value:

```

select ?s ?o ?value {
                                (?ta      ?value)

```

```

<http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>
  (?s ?p ?o) .
}

```

Repository | Queries | Utilities | Admin | User test

### Edit query

```

1 select ?s ?o ?value {
2   (?ta ?value) <http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>   (?s ?p ?o) .
3 }

```

Execute Log Query Show Plan Save as Add to repository

5 Results in 0.363 ms Information

s	o	value
<http://www.franz.com#emp0>	"2"	"2019-01-13T09:03:22"
<http://www.franz.com#emp1>	"5"	"2019-01-13T11:03:22"
<http://www.franz.com#emp0>	"3"	"2019-01-11T11:15:52"
<http://www.franz.com#emp0>	"1"	"2019-01-14T14:16:12"
<http://www.franz.com#emp0>	"2"	"2019-01-12T10:12:45"

But we are really interested just in emp0 and we would like to see the results ordered by time, that is by the attribute value, so we restrict the query to emp0 as the subject and order the results:

```

select ?o ?value {
  (?ta ?value)
  <http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>
  (<http://www.franz.com#emp0> ?p ?o) .
} order by ?value

```

## Edit query

```
1 select ?o ?value {  
2   (?ta ?value) <http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>    (<http://www.franz.com#emp0> ?p ?o) .  
3 } order by ?value
```

Execute

Log Query

Show Plan

Save as

Add to repository

4 Results in 0.630 ms

Information

o	value
"3"	"2019-01-11T11:15:52"
"2"	"2019-01-12T10:12:45"
"2"	"2019-01-13T09:03:22"
"1"	"2019-01-14T14:16:12"

There are the results for emp0, who is clearly having difficulties because the call rankings have been steadily falling over time.

Another example using timeAdded is employee salary data. In the Human Resources data, the salary of an employee is stored:

**emp0 hasSalary 50000**

Now emp0 gets a raise to 55000. So we delete the triple above and add the triple

**emp0 hasSalary 55000**

But that is not satisfactory because we have lost the salary

history. If the boss asks “How much was emp0 paid initially?” we cannot answer. There are various solutions. We could define a salary change object, with predicates effectiveDate, previousSalary, newSalary, and so on:

```
salaryChange017 forEmployee emp0
salaryChange017 effectiveDate "2019-01-12T10:12:45"
salaryChange017 oldSalary "50000"
salaryChange017 newSalary "55000"
```

**emp0 hasSalaryChange salaryChange017**

and that would work fine, but perhaps it is more setup and effort than is needed. Suppose we just have `hasSalary` triples each with a `timeAdded` attribute. Then the current salary is the latest one and the history is the ordered list. Here that idea is worked out:

```
<http://www.franz.com#emp0>    <http://www.franz.com#hasSalary>
"50000"^^<http://www.w3.org/2001/XMLSchema#integer>
{"timeAdded": "2017-01-12T10:12:45" } .

<http://www.franz.com#emp0>    <http://www.franz.com#hasSalary>
"55000"^^<http://www.w3.org/2001/XMLSchema#integer>
{"timeAdded": "2019-03-17T12:00:00" } .
```

**What is the current salary? A simple SPARQL query tells us:**

```
select ?o ?value {
                                (?ta      ?value)
<http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>
                                (<http://www.franz.com#emp0>
<http://www.franz.com#hasSalary> ?o) .
    } order by desc(?value) limit 1
```

## Edit query

```
1 select ?o ?value {  
2   (?ta ?value) <http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>  
3   (<http://www.franz.com#emp0> <http://www.franz.com#hasSalary> ?o) .  
4 } order by desc(?value) limit 1
```

Execute

Log Query

Show Plan

Save as

Add to repository

1 Result in 0.388 ms

Information

o	value
"55000"	"2019-03-17T12:00:00"

The salary history is provided by the same query without the LIMIT:

```
select ?o ?value {  
    (?ta ?value)  
<http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>  
    (<http://www.franz.com#emp0>  
<http://www.franz.com#hasSalary> ?o) .  
    } order by desc(?value)
```

## Edit query

```
1 select ?o ?value {  
2   (?ta ?value) <http://franz.com/ns/allegrograph/6.2.0/attributesNameValue>  
3   (<http://www.franz.com#emp0> <http://www.franz.com#hasSalary> ?o) .  
4 } order by desc(?value)
```

Execute

Log Query

Show Plan

Save as

Add to repository

2 Results in 0.413 ms

Information

o	value
"55000"	"2019-03-17T12:00:00"
"50000"	"2017-01-12T10:12:45"

This method of storing salary data may not easily support more complex questions which might be easily answered if we went the salaryChange object route mentioned above but if you are not looking to ask those questions, you should not do the extra work (and the risk of data errors) required.

You could use the graph of each triple for the timeAdded. All the examples above would work with minor tweaks. But there are many uses for the named graph of a triple. Attributes are available and using them for one purpose does not restrict their use for other purposes.

# Using AI and Semantic Data Lakes in Healthcare – FeibusTech Research Report



Artificial intelligence has the potential to make huge improvements in just about every aspect of healthcare. Learn how Montefiore Health Systems is using semantic data lakes, architectures, and triplestores to power AI patient-centered learning. With origins in post-9/11 municipal emergency projects, Montefiore Health Systems platform – called PALM, short for patient-centered Analytical Learning Machine – is beginning to prove itself out in the Intensive Care Unit, helping doctors save lives by flagging patients headed toward respiratory failure.

Intel and Montefiore in collaboration with FeibusTech have released a Research Brief covering Montefiore's PALM Platform (aka – The Semantic Data Lake) powered by AllegroGraph.

*"Just atop all the databases is what's known as a triplestore, or triple, construct. That's a key piece of any semantic data architecture. A triple is a three-part data series with a common grammar structure: that is, subject-predicate-object. Like, for example, John Smith has hives. Or Jill Martin takes ibuprofen."*

*"Triples are the heart and soul of graph databases, or graphs, a powerful, labor-saving approach that associates John and Jill to records of humans, hives to definitions of maladies and Ibuprofen*

*to catalogues of drugs. And then it builds databases on the fly for the task at hand based on those associations.”*

**Read the full article on Intel’s website to learn more about healthcare solutions based on AllegroGraph.**

---

## **Navigating time in knowledge graphs**

**Franz’s CEO, Jans Aasman, recently wrote the following article for InfoWorld.**



*The temporal benefits of cognitive knowledge graphs can affect almost any business problem, including basic issues of data management such as data quality, data cleansing, and integration*

*The concept of time presents several distinct challenges for data management, particularly as it applies to databases or stores. Those difficulties are related to the nature of time, which is ongoing, and its expressions in repositories. The former means data are relevant both at state (a point in time) and over periods of time, which increases the complexity.*

**Read the Full Article**



---

# The Cornerstone of Data Science: Progressive Data Modeling

From AI Business June 27, 2018

**This article covers Single Schema, Universal Taxonomies, Time Series Analysis, Accelerating Data Science and features some thought leadership from Franz Inc.'s CEO, Jans Aasman:**

*'Contemporary data science and artificial intelligence requirements simply can't wait for this ongoing, dilatory process. According to Jans Aasman, CEO of Franz, they no longer have to. By deploying what Aasman called an "events-based approach to schema", companies can model datasets with any number of differences alongside one another for expedited enterprise value.'*

*'The resulting schema is simplified, uniform, and useful in multiple ways. "You achieve two goals," Aasman noted. "One is you define what data you trust to be in the main repository to have all the truth. The second thing is you make your data management a little more uniform. By doing those two things your AI and your data science will become better, because the data that goes into them is better."'*

**Dr. Aasman goes on to note:**

*'The events-based schema methodology only works with enterprise taxonomies—or at least with taxonomies spanning the different sources included in a specific repository, such as a Master Data Management hub. Taxonomies are necessary so*

*that “the type of event can be specified,” Aasman said.’*

*‘Moreover, taxonomies are indispensable for clarifying terms and their meaning across different data formats, which may represent similar concepts in distinct ways. Therefore, practically all objects in a database should be “taxonomy based” Aasman said, because these hierarchical classifications enable organizations to query their repositories via this uniform schema.’*

Read the full article over at [AI Business](#).



---

# Optimizing Fraud Management with AI Knowledge Graphs

From Global Banking and Finance Review – July 12, 2018

**This article discusses Knowledge Graphs for Anti-Money Laundering (AML), Suspicious Activity Reports (SAR), counterfeiting and social engineering falsities, as well as synthetic, first-party, and card-not-present fraud.**

*By compiling fraud-related data into an AI knowledge graph, risk management personnel can also triage those alerts for the right action at the right time. They also get the additive benefit of reusing this graph to decrease other*

*risks for security, loans, or additional financial purposes.*

**Dr. Aasman goes on to note:**

*By incorporating AI, these threat maps yields a plethora of information for actually preventing fraud. Supervised learning methods can readily identify what events constitute fraud and which don't; many of these involve classic machine learning. Unsupervised learning capabilities are influential in determining normal user behavior then pinpointing anomalies contributing to fraud. Perhaps the most effective way AI underpins risk management knowledge graphs is in predicting the likelihood—and when—a specific fraud instance will take place. Once organizations have data for customers, events, and fraud types over a length of time (which could be in as little as a month in the rapidly evolving financial crimes space), they can compute the co-occurrence between events and fraud types.*

Read the full article over at [Global Banking and Finance Review](#).



---

# Why dynamically visualizing relationships in data matters

Franz's CEO, Jans Aasman, recently wrote the following article for InfoWorld.



*The ability to visualize data, their relationships to one another and connections to business objectives gives organizations the power to uncover insights that would otherwise elude them.*

*Data visualizations have pervaded nearly every aspect of today's data landscape. Initially conceived of as a means of best presenting analytics results, data visualizations have evolved to affect everything from drag-and-drop approaches to data preparation to visual mechanisms for issuing queries. The ability to visualize data, their relationships to one another and connections to business objectives is central to the notion of data exploration, in which users manipulate these graphical representations for greater understanding of data's overall meaning. Data visualizations are vital for exploring knowledge graphs, which determine relationships between even seemingly unrelated datasets to indicate their relevance to specific tasks.*

**Read the Full Article**

---

## **How AI Boosts Human Expertise at Wolters Kluwer**



**Wolters Kluwer, a long time AllegroGraph customer, recently spoke with Alex Woodie at Datanami to describe how they are using AI tools such as AllegroGraph:**

*Thousands of companies around the world rely on Wolters Kluwer's practice management software to automate core aspects of their businesses. That includes doctor's offices that use its software make healthcare decisions in a clinical setting, corporate law offices that use its software to understand M&A activities, and accounting firms that use its*

software to craft tax strategies for high net-worth clients.

Wolters Kluwer is embedding a range of AI capabilities – including deep learning and graph analytics – across multiple product lines. For example, its Legalview Bill Analyzer software helps to identify errors in legal bills sent from outside law firms to the corporate counsels of large companies. The typical recovery rate for people reviewing bills manually is 1% to 2%. By adding machine learning technology to the product the recovery rate jumps to 7% to 8%, which can translate into tens of millions of dollars.

Wolters Kluwer is using graph analytic techniques to accelerate the knowledge discovery process for its clients across various professions. **The company has tapped Franz's AllegroGraph software** to help it drive new navigational tools for helping customers find answers to their questions.

By arranging known facts and concepts as **triples in the AllegroGraph database** and then exposing those structures to users through a traditional search engine dialog box, Wolters Kluwer is able to surface related insights in a much more interactive manner.

"We're providing this live feedback. As you're typing, we're providing question and suggestions for you live," Tatham said. **"AllegroGraph gives us a performant way** to be able to just work our way through the whole knowledge model and come up with suggestion to the user in real time."

**Read the full article over at Datanami.**

---

# Solidifying security analytics with artificial intelligence knowledge graphs

Franz's CEO, Jans Aasman, recently wrote the following article for InfoWorld.



*AI knowledge graphs can augment security analytics by linking knowledge together to pinpoint relationships and patterns related to security issues pertinent to an organization.*

*Each successive instance of data compromises (and their escalating repercussions) is a veritable case study for the necessity of security analytics. With increasing regulations and new security threats amassing daily, the deployment of user behavior analytics may well become the most viable tool for protecting enterprise data.*

**[Read the Full Article](#)**

---

## The Most Secure Graph Database Available

Triples offer a way of describing model elements and relationships between them. In some cases, however, it is also convenient to be able to store data that is associated with a triple as a whole rather than with a particular element. For instance one might wish

to record the source from which a triple has been imported or access level necessary to include it in query results. Traditional solutions of this problem include using graphs, RDF reification or triple IDs. All of these approaches suffer from various flexibility and performance issues. For this reason AllegroGraph offers an alternative: triple attributes.

Attributes are key-value pairs associated with a triple. Keys refer to attribute definitions that must be added to the store before they are used. Values are strings. The set of legal values of an attribute can be constrained by the definition of that attribute. It is possible to associate multiple values of a given attribute with a single triple.

Possible uses for triple attributes include:

- *Access control: It is possible to instruct AllegroGraph to prevent an user from accessing triples with certain attributes.*
- *Sharding: Attributes can be used to ensure that related triples are always placed in the same shard when AllegroGraph acts as a distributed triple store.*

Like all other triple components, attribute values are immutable. They must be provided when the triple is added to the store and cannot be changed or removed later.

To illustrate the use of triple attributes we will construct an artificial data set containing a log of information about contacts detected by a submarine at a single moment in time.

## Managing attribute definitions

Before we can add triples with attributes to the store we must create appropriate attribute definitions.

First let's open a connection

```
from franz.openrdf.connect import ag_connect

conn = ag_connect('python-tutorial', create=True, clear=True)
```

Attribute definitions are represented by **AttributeDefinition** objects. Each definition has a name, which must be unique, and a few optional properties (that can also be passed as constructor arguments):

- *allowed\_values: a list of strings. If this property is set*



then only the values from this list can be used for the defined attribute.

- `ordered`: a boolean. If true then attribute value comparisons will use the ordering defined by `allowed_values`. The default is false.
- `minimum_number`, `maximum_number`: integers that can be used to constrain the cardinality of an attribute. By default there are no limits.

Let's define a few attributes that we will later use to demonstrate various attribute-related capabilities of AllegroGraph. To do this, we will use the `setAttributeDefinition()` method of the connection object.

```
from franz.openrdf.repository.attributes import AttributeDefinition
```

```
# A simple attribute with no constraints governing the set  
# of legal values or the number of values that can be  
# associated with a triple.
```

```
tag = AttributeDefinition(name='tag')
```

```
# An attribute with a limited set of legal values.  
# Every bit of data can come from multiple sources.  
# We encode this information in triple attributes,  
# since it refers to the tripe as a whole. Another  
# way of achieving this would be to use triple ids  
# or RDF reification.
```

```
source = AttributeDefinition(  
    name='source',  
    allowed_values=['sonar', 'radar', 'esm', 'visual'])
```

```
# Security level - notice that the values are ordered  
# and each triple *must* have exactly one value for  
# this attribute. We will use this to prevent some  
# users from accessing classified data.
```

```
level = AttributeDefinition(  
    name='level',  
    allowed_values=['low', 'medium', 'high'],  
    ordered=True,  
    minimum_number=1,  
    maximum_number=1)
```

```
# An attribute like this could be used for sharding.  
# That would ensure that data related to a particular  
# contact is never partitioned across multiple shards.  
# Note that this attribute is required, since without  
# it an attribute-sharded triple store would not know  
# what to do with a triple.
```

```

contact = AttributeDefinition(
    name='contact',
    minimum_number=1,
    maximum_number=1)

# So far we have created definition objects, but we
# have not yet sent those definitions to the server.
# Let's do this now.
conn.setAttributeDefinition(tag)
conn.setAttributeDefinition(source)
conn.setAttributeDefinition(level)
conn.setAttributeDefinition(contact)

# This line is not strictly necessary, because our
# connection operates in autocommit mode.
# However, it is important to note that attribute
# definitions have to be committed before they can
# be used by other sessions.
conn.commit()

```

It is possible to retrieve the list of attribute definitions from a repository by using the **getAttributeDefinitions()** method:

```

for attr in conn.getAttributeDefinitions():
    print('Name: {0}'.format(attr.name))
    if attr.allowed_values:
        print('Allowed values: {0}'.format(
            ', '.join(attr.allowed_values)))
        print('Ordered: {0}'.format(
            'Y' if attr.ordered else 'N'))
    print('Min count: {0}'.format(attr.minimum_number))
    print('Max count: {0}'.format(attr.maximum_number))
    print()

```

Notice that in cases where the maximum cardinality has not been explicitly defined, the server replaced it with a default value. In practice this value is high enough to be interpreted as ‘no limit’.

```

Name: tag
Min count: 0
Max count: 1152921504606846975

```

```

Name: source
Allowed values: sonar, radar, esm, visual
Min count: 0
Max count: 1152921504606846975
Ordered: N

```

```
Name: level
Allowed values: low, medium, high
Ordered: Y
Min count: 1
Max count: 1
```

```
Name: contact
Min count: 1
Max count: 1
```

Attribute definitions can be removed (provided that the attribute is not used by the static attribute filter, which will be discussed later) by calling **deleteAttributeDefinition()**:

```
conn.deleteAttributeDefinition('tag')
defs = conn.getAttributeDefinitions()
print(', '.join(sorted(a.name for a in defs)))
```

```
contact, level, source
```

## Adding triples with attributes

Now that the attribute definitions have been established we can demonstrate the process of adding triples with attributes. This can be achieved using various methods. A common element of all these methods is the way in which triple attributes are represented. In all cases dictionaries with attribute names as keys and strings or lists of strings as values are used.

When **addTriple()** is used it is possible to pass attributes in a keyword parameter, as shown below:

```
ex = conn.namespace('ex://')
conn.addTriple(ex.S1, ex.cls, ex.Udaloy, attributes={
    'source': 'sonar',
    'level': 'low',
    'contact': 'S1'
})
```

The **addStatement()** method works in similar way. Note that it is not possible to include attributes in the **Statement** object itself.

```
from franz.openrdf.model import Statement
```

```
s = Statement(ex.M1, ex.cls, ex.Zumwalt)
conn.addStatement(s, attributes={
    'source': ['sonar', 'esm'],
    'level': 'medium',
    'contact': 'M1'
})
```

When adding multiple triples with **addTriples()** one can add a fifth element to each tuple to represent attributes. Let us illustrate this by adding an aircraft to our dataset.

```
conn.addTriples(
    [(ex.R1, ex.cls, ex['Ka-27'], None,
      {'source': 'radar',
       'level': 'low',
       'contact': 'R1'}),
     (ex.R1, ex.altitude, 200, None,
      {'source': 'radar',
       'level': 'medium',
       'contact': 'R1'})])
```

When all or most of the added triples share the same attribute set it might be convenient to use the `attributes` keyword parameter. This provides default values, but is completely ignored for all tuples that already contain attributes (the dictionaries are not merged). In the example below we add a triple representing an aircraft carrier and a few more triples that specify its position. Notice that the first triple has a lower security level and multiple sources. The common ‘contact’ attribute could be used to ensure that all this data will remain on a single shard.

```
conn.addTriples(
    [(ex.M2, ex.cls, ex.Kuznetsov, None, {
        'source': ['sonar', 'radar', 'visual'],
        'contact': 'M2',
        'level': 'low',
    }),
     (ex.M2, ex.position, ex.pos343),
     (ex.pos343, ex.x, 430.0),
     (ex.pos343, ex.y, 240.0)],
    attributes={
        'contact': 'M2',
        'source': 'radar',
        'level': 'medium'
    })
```

Another method of adding triples with attributes is to use the NQX

file format. This works both with **addFile()** and **addData()** (illustrated below):

```
from franz.openrdf.rio.rdfformat import RDFFormat

conn.addData('''
    <ex://S2> <ex://cls> <ex://Alpha> \
    {"source": "sonar", "level": "medium", "contact": "S2"} .
    <ex://S2> <ex://depth> "300" \
    {"source": "sonar", "level": "medium", "contact": "S2"} .
    <ex://S2> <ex://speed_kn> "15.0" \
    {"source": "sonar", "level": "medium", "contact": "S2"} .
''', rdf_format=RDFFormat.NQX)
```

When importing from a format that does not support attributes, it is possible to provide a common set of attribute values with a keyword parameter:

```
from franz.openrdf.rio.rdfformat import RDFFormat

conn.addData('''
    <ex://V1> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 100 ;
        <ex://speed_kn> 12.0e+8 .
    <ex://V2> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 200 ;
        <ex://speed_kn> 12.0e+8 .
    <ex://V3> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 300;
        <ex://speed_kn> 12.0e+8 .
    <ex://V4> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 400 ;
        <ex://speed_kn> 12.0e+8 .
    <ex://V5> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 500 ;
        <ex://speed_kn> 12.0e+8 .
    <ex://V6> <ex://cls> <ex://Walrus> ;
        <ex://altitude> 600 ;
        <ex://speed_kn> 12.0e+8 .
''', attributes={
    'source': 'visual',
    'level': 'high',
    'contact': 'a therapist'})
```

The data above represents six visually observed Walrus-class submarines, flying at different altitudes and well above the speed of light. It has been highly classified to conceal the fact that someone has clearly been drinking while on duty – after all there

are only four Walrus-class submarines currently in service, so the observation is obviously incorrect.

## Retrieving attribute values

We will now print all the data we have added to the store, including attributes, to verify that everything worked as expected. The only way to do that is through a SPARQL query using the appropriate [magic property](#) to access the attributes. The query below binds a literal containing a JSON representation of triple attributes to the `?a` variable:

```
import json

r = conn.executeTupleQuery('''
    PREFIX attr: <http://franz.com/ns/allegrograph/6.2.0/>
    SELECT ?s ?p ?o ?a {
        ?s ?p ?o .
        ?a attr:attributes (?s ?p ?o) .
    } ORDER BY ?s ?p ?o''')
with r:
    for row in r:
        print(row['s'], row['p'], row['o'])
        print(json.dumps(json.loads(row['a'].label),
                          sort_keys=True,
                          indent=4))
```

The result contains all the expected triples with pretty-printed attributes.

```
<ex://M1> <ex://cls> <ex://Zumwalt>
{
  "contact": "M1",
  "level": "medium",
  "source": [
    "esm",
    "sonar"
  ]
}
<ex://M2> <ex://cls> <ex://Kuznetsov>
{
  "contact": "M2",
  "level": "low",
  "source": [
    "visual",
    "radar",
    "sonar"
```

```
]
}
<ex://M2> <ex://position> <ex://pos343>
{
  "contact": "M2",
  "level": "medium",
  "source": "radar"
}
<ex://R1> <ex://altitude> "200"^^...
{
  "contact": "R1",
  "level": "medium",
  "source": "radar"
}
<ex://R1> <ex://cls> <ex://Ka-27>
{
  "contact": "R1",
  "level": "low",
  "source": "radar"
}
<ex://S1> <ex://cls> <ex://Udaloy>
{
  "contact": "S1",
  "level": "low",
  "source": "sonar"
}
<ex://S2> <ex://cls> <ex://Alpha>
{
  "contact": "S2",
  "level": "medium",
  "source": "sonar"
}
<ex://S2> <ex://depth> "300"
{
  "contact": "S2",
  "level": "medium",
  "source": "sonar"
}
<ex://S2> <ex://speed_kn> "15.0"
{
  "contact": "S2",
  "level": "medium",
  "source": "sonar"
}
<ex://V1> <ex://altitude> "100"^^...
{
  "contact": "a therapist",
  "level": "high",
  "source": "visual"
}
```

```

<ex://V1> <ex://cls> <ex://Walrus>
{
  "contact": "a therapist",
  "level": "high",
  "source": "visual"
}
<ex://V1> <ex://speed_kn> "1.2E9"^^...
{
  "contact": "a therapist",
  "level": "high",
  "source": "visual"
}
...
<ex://pos343> <ex://x> "4.3E2"^^...
{
  "contact": "M2",
  "level": "medium",
  "source": "radar"
}
<ex://pos343> <ex://y> "2.4E2"^^...
{
  "contact": "M2",
  "level": "medium",
  "source": "radar"
}

```

## Attribute filters

Triple attributes can be used to provide fine-grained access control. This can be achieved by using [static attribute filters](#).

Static attribute filters are simple expressions that control which triples are visible to a query based on triple attributes. Each repository has a single, global attribute filter that can be modified using `setAttributeFilter()`. The values passed to this method must be either strings (the syntax is described in the documentation of [static attribute filters](#)) or filter objects.

Filter objects are created by applying set operators to 'attribute sets'. These can then be combined using filter operators.

An attribute set can be one of the following:

- *a string or a list of strings: represents a constant set of values.*
- *TripleAttribute.name: represents the value of the name attribute associated with the currently inspected triple.*



- *UserAttribute.name*: represents the value of the name attribute associated with current query. User attributes will be discussed in more detail later.

Available set operators are shown in the table below. All classes and functions mentioned here can be imported from the `franz.openrdf.repository.attributes` package:

Syntax	Meaning
<code>Empty(x)</code>	True if the specified attribute set is empty.
<code>Overlap(x, y)</code>	True if there is at least one matching value between the two attribute sets.
<code>Subset(x, y), x &lt;&lt; y</code>	True if every element of <i>x</i> can be found in <i>y</i>
<code>Superset(x, y), x &gt;&gt; y</code>	True if every element of <i>y</i> can be found in <i>x</i>
<code>Equal(x, y), x == y</code>	True if <i>x</i> and <i>y</i> have exactly the same contents.
<code>Lt(x, y), x &lt; y</code>	True if both sets are singletons, at least one of the sets refers to a triple or user attribute, the attribute is ordered and the value of the single element of <i>x</i> occurs before the single value of <i>y</i> in the <code>lowed_values</code> list of the attribute.
<code>Le(x, y), x &lt;= y</code>	True if <i>y</i> < <i>x</i> is false.
<code>Eq(x, y)</code>	True if both <i>x</i> < <i>y</i> and <i>y</i> < <i>x</i> are false. Note that using the <code>==</code> Python operator translates to <i>Eqauls</i> , not <i>Eq</i> .
<code>Ge(x, y), x &gt;= y</code>	True if <i>x</i> < <i>y</i> is false.
<code>Gt(x, y), x &gt; y</code>	True if <i>y</i> < <i>x</i> .

Note that the overloaded operators only work if at least one of the attribute sets is a `UserAttribute` or `TripleAttribute` reference –



connection and are sent to the server with each query. The static attribute filter can refer to these and compare them with triple attributes. Thus we can use code presented below to create a filter which ensures that a connection only accesses data at or below the chosen clearance level.

```
conn.setUserAttributes({'level': 'low'})
conn.setAttributeFilter(
    TripleAttribute.level <= UserAttribute.level)
conn.executeTupleQuery(
    'select ?class { ?s <ex://cls> ?class } order by ?class',
    output=True)
```

We can see that the output here contains only contacts with the access level of *low*. It omits the destroyer and Alpha submarine (these require *medium* level) as well as the top-secret Walruses.

```
-----
| class          |
=====
| ex://Ka-27     |
| ex://Kuznetsov |
| ex://Udaloy    |
|                |
-----
```

The main advantage of the code presented above is that the filter can be set globally during the application setup and access control can then be achieved by varying user attributes on connection objects.

Let us now remove the attribute filter to prevent it from interfering with other examples. We will use the **clearAttributeFilter()** method.

```
conn.clearAttributeFilter()
```

It might be useful to change connection's attributes temporarily for the duration of a single code block and restore prior attributes after that. This can be achieved using the **temporaryUserAttributes()** method, which returns a context manager. The example below illustrates its use. It also shows how to use **getUserAttributes()** to inspect user attributes.

```
with conn.temporaryUserAttributes({'level': 'high'}):
    print('User attributes inside the block:')
    for k, v in conn.getUserAttributes().items():
```

```
        print('{0}: {1}'.format(k, v))
    print()
    print('User attributes outside the block:')
    for k, v in conn.getUserAttributes().items():
        print('{0}: {1}'.format(k, v))
```

```
User attributes inside the block:
level: high
```

```
User attributes outside the block:
level: low »
```

---

# The marvels of an event-based schema

Franz's CEO, Jans Aasman, recently wrote the following article for InfoWorld.



*When working with various data types at the speed of big data, this method is ideal for integrating and aggregating assorted information for the holistic value it provides.*

*The issue of schema—and what is frequently perceived as its inherent difficulties—is becoming more important every day. Organizations are increasingly encountering decentralized computing environments typified by semi-structured or unstructured external data of varying formats, often requiring integration with internal, structured data for immediate business value.*

**Read the Full Article**